



GMEXG-P-02-FM

1" WATER

FM APPROVED Certified

managed by control unit [code *GMCU1610SD*]



Complies with **ATEX Directive 2014/34/EU - Category 3D/3G**

Complete with:

- 1" ball valve with position sensor complying with **ATEX Directive 2014/34/EU**
- 1000-µm water filter
- pressure gauge complying with ATEX **Directive 2014/34/EU - Category 3D/3G**
- 1" solenoid valve with coil complying with **ATEX Directive 2014/34/EU**
- die-cast aluminium enclosure, painted RAL3000, which contains the electronics that allow the management from the control unit
- water temperature sensor
- 2 nipples from 1" to 3/4" and roll of Teflon

Fully wired in the laboratory, electronically and hydraulically tested.

ACCESSORIES:



GMSUP5D-FXU

Non-invasive pipe fixing support.
Suitable for pipes with diameter greater than 150 mm
and a thickness less than 1.9 mm.



ACCESSORIES:

GMTG34-040, GMTG34-060, GMTG34-075, GMTG34-100, GMTG34-125, GMTG34-150, GMTG34-175

Pair of red rubber tubes

FM APPROVED Certified

to connect the water extinguishing [GM-EXG-P-02] to the sprayer nozzles [GMUGS-CVO-12-FM]



GMUGS-CVO-12-FM

Sprayer nozzle with lock. Cone-shaped jet

FM APPROVED Certified



GMSUP5D

Non-invasive pipe fixing support.

Suitable for pipes with diameter greater than 150 mm and a thickness less than 1.9 mm.

Specifics for sprayer nozzle code GMUGS-CVO-12-FM

FM APPROVED Certified - TÜV Certified

