



## GMEXG-P-02-FM

### 1" WATER EXTINGUISHING SET

FM APPROVED Certified

managed by control unit [code GMCU1610SD]



Complies with **ATEX Directive 2014/34/EU - Category 3D/3G**

Complete with:

- 1" ball valve with position sensor complying with **ATEX Directive 2014/34/EU**
- 1000-µm water filter
- pressure gauge complying with **ATEX Directive 2014/34/EU - Category 3D/3G**
- 1" solenoid valve with coil complying with **ATEX Directive 2014/34/EU**
- die-cast aluminium enclosure, painted RAL3000, containing the electronics that allow the management from the control unit
- water temperature sensor
- 2 nipples from 1" to ¾" and roll of Teflon

Fully wired, electronically tested and hydraulically tested in our laboratory.

#### ACCESSORIES:



#### GMSUP5D-FXU

Non-invasive mounting kit.

Suitable for ducts with diameter greater than 150 mm and a thickness less than 1.9 mm.



## ACCESSORIES:

### GMTG34-040, GMTG34-060, GMTG34-075, GMTG34-100, GMTG34-125, GMTG34-150, GMTG34-175

Pair of red rubber tubes

to connect the water extinguishing set [GM-EXG-P-02]  
to the sprayer nozzles [GMUGS-CVO-I2-FM]

**FM APPROVED** Certified



### GMUGS-CVO-I2-FM

Spray nozzle with shutter. Cone-shaped jet

**FM APPROVED** Certified



### GMSUP5D

Non-invasive.

Suitable for ducts with diameter greater than 150 mm and a thickness less than 1.9 mm.

Specific for spray nozzle code GMUGS-CVO-I2-FM

**FM APPROVED** Certified - **TÜV** Certified

