



## PIPES FOR THE CONNECTION BETWEEN THE GMEXG-P-02-FM EXTINGUISHING GROUP AND THE GMUGS-CVO-I2-FM WATER SPRAY NOZZLES

### PAIR OF RED RUBBER PIPES

Operating temperature: -30°C - +110°C - Maximum pressure 20 bar

Replace every five years following production date

Complete with two 3/4" FD connectors in galvanized brass with flat face and paper gasket

FM APPROVED Certified



### GMTG34-040

For pipes with diameter 150-400 mm.

Rubber pipes 13 x 20 L = 600 mm

### GMTG34-060

For pipes with diameter 400-600 mm.

Rubber pipes 13 x 20 L = 800 mm

### GMTG34-075

For pipes with diameter 600-750 mm.

Rubber pipes 13 x 20 L = 1000 mm

### GMTG34-100

For pipes with diameter 750-1000 mm.

Rubber pipes 13 x 20 L = 1200 mm

### GMTG34-125

For pipes with diameter 1000-1250 mm.

Rubber pipes 13 x 20 L = 1400 mm

### GMTG34-150

For pipes with diameter 1250-1500 mm.

Rubber pipes 13 x 20 L = 1600 mm

### GMTG34-175

For pipes with diameter 1500-1750 mm.

Rubber pipes 13 x 20 L = 2000 mm

#### Note:

- 1) The rubber pipes listed above may also be sold separately, only as spare parts.  
For quotes, contact the sales office.
- 2) These pipes **CANNOT** be used with nozzles code **GMUGS-CVO-M-IX**



## ACCESSORIES:



### GMUGS-CVO-12-FM

Sprayer nozzle with lock. Cone-shaped jet  
**FM APPROVED Certified**



### GMSUP5D

Non-invasive attachment system  
 specifically for sprayer nozzle  
 GMUGS-CVO-12- FM  
**FM APPROVED Certified - TÜV Certified**



### GMEXG-P-02-FM 1" WATER EXTINGUISHING

**FM APPROVED Certified**  
 managed by control unit [code *GMCU1610SD*]  
 Complies with **ATEX Directive 2014/34/EU**  
**Category 3D/3G**



### GMSUP5D-FXU

Non-invasive pipe fixing support  
 For the GMEXG-P-02-FM extinguishing group  
 Complies with **ATEX Directive 2014/34/EU**  
**Category 2D/2G**  
**FM APPROVED Certified - TÜV Certified**

