



## GM-CT2-P01

### POLYCARBONATE ENCLOSURE for microprocessor module

[versions: GMPID001-STN, GMPID001 V1.4-1, GMPID001 V1.4-2  
GMPID002-TRB-003, GMPID002-TRB-005,  
GMPID002-TRB6, GMPID002-ULM, GMVDUST01]

**Protection: IP65**

**Includes:** Module attachment flange

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

**Excludes microprocessor module**



## GM-CT2-PG

### POLYCARBONATE ENCLOSURE for microprocessor module with hose connectors

[versions: GM-PID002-D1-K2, GM-FLOW02-xx all versions  
GM-PID001-Dxxx all versions]

**Protection: IP65**

**Includes:** 2 brass hose connectors ø4x6mm

+ module attachment flange

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

**Excludes microprocessor module**



## GM-CT2-PRJ

### POLYCARBONATE ENCLOSURE for microprocessor module with RJ45 port for remote connection

[versions: GMPID002-TRB-UE-003, GMPID002-TRB-UE-005,  
GMPID002-TRB6-UE, GMPID002-ULM-UE]

**Protection: IP65**

**Includes:** female RJ45 port outside the enclosure

+ male RJ45 socket (including internal wiring)

+ module attachment flange

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

**Excludes microprocessor module**



## GM-CT2-P01S-RJ

### POLYCARBONATE ENCLOSURE for microprocessor module with hose connectors and RJ45 port for remote connection

[versions: GM-PID002-D1-K2-UE,  
GM-FLOW02-UE-xx all versions (NO AP versions)]

**Protection: IP65**

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

**Includes:** 2 brass hose connectors ø4x6mm

+ female RJ45 port outside the enclosure

+ male RJ45 socket (including internal wiring)

+ module attachment flange

**Excludes microprocessor module**

