



GM-CT2-PO1

POLYCARBONATE ENCLOSURE for microprocessor module

[versions: GMPID001-STN, GMPID001 V1.4, GMPID002-TRB-xxx]

Protection: IP65

Includes: Module attachment flange

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

No microprocessor module included



GM-CT2-PG

POLYCARBONATE ENCLOSURE for microprocessor module with hose connectors

[versions: GM-PID002-D1-K2, GM-FLOW02-xx all versions]

GM-PID001-Dxxx all versions]

Protection: IP65

Includes: 2 brass hose connectors ø4x6mm

+ module attachment flange

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

No microprocessor module included



GM-CT2-PRJ

POLYCARBONATE ENCLOSURE for microprocessor module with RJ45 port for remote connection

[versions: GMPID002-TRB-003-UE, GMPID002-TRB-005-UE, GMPID002-TRB6-UE]

Protection: IP65

Includes: female RJ45 port outside the enclosure

+ male RJ45 socket (including internal wiring)

+ module attachment flange

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

No microprocessor module included



GM-CT2-PO1S-RJ

POLYCARBONATE ENCLOSURE for microprocessor modules with hose connectors and

RJ45 port for remote connection

[versions: GM-FLOW02-UE-xx (NO AP version)]

Protection: IP65

Dimensions: W x D x H = 160 mm x 166 mm x 105mm

Includes: 2 brass hose connectors ø4x6mm

+ female RJ45 port outside the enclosure

+ male RJ45 socket (including internal wiring)

+ module attachment flange

No microprocessor module included

